



Change detection in polarimetric SAR images using complex Wishart distributed matrices

Conradsen, Knut; Nielsen, Allan Aasbjerg; Skriver, Henning

Publication date:
2015

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Conradsen, K., Nielsen, A. A., & Skriver, H. (2015). *Change detection in polarimetric SAR images using complex Wishart distributed matrices*. Abstract from 37th Danish Symposium on Applied Statistics, Kgs. Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Change detection in polarimetric SAR images using complex Wishart distributed matrices

Knut Conradsen¹, Allan Aasbjerg Nielsen¹ and Henning Skriver²
Technical University of Denmark

¹DTU Compute – Department of Applied Mathematics and Computer Science

²DTU Space – National Space Institute

<http://people.compute.dtu.dk/alan>

alan@dtu.dk

In surveillance it is important to be able to detect natural or man-made changes, e.g., based on sequences of satellite or air borne images of the same area taken at different times. The mapping capability of synthetic aperture radar (SAR) is independent of, e.g., cloud cover, and thus this technology holds a strong potential for change detection studies in remote sensing. In polarimetric synthetic aperture radar we measure the amplitude and phase of backscattered signals in four combinations of the linear horizontal and vertical receive and transmit polarizations. These signals form a complex scattering matrix, and after suitable preprocessing the outcome at each picture element (pixel) may be represented as a 3 by 3 Hermitian matrix following a complex Wishart distribution.

One approach to solving the change detection problem based on SAR images is therefore to apply suitable statistical tests in the complex Wishart distribution. We propose a set-up for a systematic solution to the (practical) problems using the likelihood ratio test statistics. We show some examples based on a time series of images with 1024 by 1024 pixels.